



Galvanized Strand



Galvanized Steel Wire Strand Per ASTM A475-03

Nominal Diameter (in)	Construction	Nominal Diameter of Coated Wires in Strand (in)	Approx. Weight per 1000ft (lbs)	Minimum Breaking Load (lbs)				
				Utilities Grade	Common Grade	Siemens Martin Grade	High Strength Grade	Extra High Strength Grade
3/16	1 X 7	0.062	73	---	1,150	1,900	2,850	3,990
3/16	1 X 7	0.065	80	2,400	---	---	---	---
7/32	1 X 7	0.072	98	---	1,540	2,560	3,850	5,400
1/4	1 X 3	0.120	117	3,150	---	---	---	---
1/4	1 X 3	0.120	117	4,500	---	---	---	---
1/4	1 X 7	0.080	121	---	1,900	3,150	4,750	6,650
9/32	1 X 7	0.093	164	4,600	2,570	4,250	6,400	8,950
5/16	1 X 3	0.145	171	6,500	---	---	---	---
5/16	1 X 7	0.104	205	---	3,200	5,350	8,000	11,200
5/16	1 X 7	0.109	225	6,000	---	---	---	---
3/8	1 X 3	0.165	220	8,500	---	---	---	---
3/8	1 X 7	0.120	273	11,500	4,250	6,950	10,800	15,400
7/16	1 X 7	0.145	399	18,000	5,700	9,350	14,500	20,800
1/2	1 X 7	0.165	517	25,000	7,400	12,100	18,800	26,900
9/16	1 X 7	0.188	670	---	9,600	15,700	24,500	35,000
5/8	1 X 7	0.207	813	---	11,600	19,100	29,600	42,400
3/4	1 X 19	0.150	1,155	---	16,000	26,200	40,800	58,300