

- Forged Carbon Steel Bodies
- Alloy Pins
- Heat Treated

Screw Pin Anchor Shackles Hot Dipped Galvanized



Meets Federal Spec
RR-C-271d, Type IV A
Grade A, Class 2

Size (in)	Pin Dia (in)	Inside Width at pin (in)	Inside Width at bow (in)	Working Load Limit (tons)	Approx Weight Ea (lbs)
3/16	1/4	3/8	19/32	1/3	.05
1/4	5/16	1/2	3/4	1/2	.10
5/16	3/8	9/16	1	3/4	.19
3/8	7/16	11/16	1-1/8	1	.25
7/16	1/2	3/4	1-1/4	1-1/2	.50
1/2	5/8	13/16	1-5/16	2	.75
5/8	3/4	1-1/16	1-11/16	3-1/4	1.44
3/4	7/8	1-1/4	2	4-3/4	2.50
7/8	1	1-7/16	2-1/4	6-1/2	3.50
1	1-1/8	1-11/16	2-5/8	8-1/2	5.25
1-1/8	1-1/4	1-7/8	3	9-1/2	7.25
1-1/4	1-3/8	2	3-3/8	12	9.75
1-3/8	1-1/2	2-1/4	3-5/8	13-1/2	13.25
1-1/2	1-5/8	2-3/8	3-7/8	17	17.70
1-3/4	2	2-7/8	5	25	30.38
2	2-1/4	3-1/4	5-3/4	35	45.00

See These In Our
Stainless Steel
Section

Bolt Type Anchor Shackles Hot Dipped Galvanized



Meets Federal Spec
RR-C-271d, Type IV A
Grade A, Class 3

Size (in)	Pin Dia (in)	Inside Width at pin (in)	Inside Width at bow (in)	Working Load Limit (tons)	Approx Weight Ea (lbs)
1/2	5/8	13/16	1-5/16	2	.75
5/8	3/4	1-1/16	1-11/16	3-1/4	1.44
3/4	7/8	1-1/4	2	4-3/4	2.50
7/8	1	1-7/16	2-1/4	6-1/2	3.50
1	1-1/8	1-11/16	2-5/8	8-1/2	5.25
1-1/8	1-1/4	1-7/8	3	9-1/2	7.25
1-1/4	1-3/8	2	3-3/8	12	11.50
1-3/8	1-1/2	2-1/4	3-5/8	13-1/2	15.00
1-1/2	1-5/8	2-3/8	3-7/8	17	18.70
1-3/4	2	2-7/8	5	25	30.38
2	2-1/4	3-1/4	5-3/4	35	45.00
2-1/2	2-3/4	4-1/8	7-1/4	55	85.75
3	3-1/4	5	7-7/8	85	145.00