

Chain Shackles



- Forged Carbon Steel Bodies
- Alloy Pins
- Heat Treated



Screw Pin Chain Shackles Hot Dipped Galvanized



Meets Federal Spec
RR-C-271d, Type IV B
Grade A, Class 2

Size (in)	Pin Dia (in)	Inside Width at pin (in)	Working Load Limit (tons)	Approx Weight Ea (lbs)
1/4	5/16	1/2	1/2	.11
5/16	3/8	9/16	3/4	.17
3/8	7/16	11/16	1	.28
7/16	1/2	3/4	1-1/2	.43
1/2	5/8	13/16	2	.59
5/8	3/4	1-1/16	3-1/4	1.25
3/4	7/8	1-1/4	4-3/4	2.63
7/8	1	1-7/16	6-1/2	3.16
1	1-1/8	1-11/16	8-1/2	4.75
1-1/8	1-1/4	1-7/8	9-1/2	6.75
1-1/4	1-3/8	2	12	9.06
1-3/8	1-1/2	2-1/4	13-1/2	11.63
1-1/2	1-5/8	2-3/8	17	15.95
1-3/4	2	2-7/8	25	26.75
2	2-1/4	3-1/4	35	42.30

See These In Our
Stainless Steel
Section

Bolt Type Chain Shackles Hot Dipped Galvanized



Meets Federal Spec
RR-C-271d, Type IV B
Grade A, Class 3

Size (in)	Pin Dia (in)	Inside Width at pin (in)	Working Load Limit (tons)	Approx Weight Ea (lbs)
7/16	1/2	3/4	1-1/2	.49
1/2	5/8	13/16	2	.75
5/8	3/4	1-1/16	3-1/4	1.47
3/4	7/8	1-1/4	4-3/4	2.52
7/8	1	1-7/16	6-1/2	3.85
1	1-1/8	1-11/16	8-1/2	5.55
1-1/8	1-1/4	1-7/8	9-1/2	7.60
1-1/4	1-3/8	2	12	10.81
1-3/8	1-1/2	2-1/4	13-1/2	13.75
1-1/2	1-5/8	2-3/8	17	18.50
1-3/4	2	2-7/8	25	31.40
2	2-1/4	3-1/4	35	46.75