

Eye Bolts & Eye Nuts



Regular Nut Eye Bolts Hot Dipped Galvanized



| Shank Diameter X Shank Length (in) | Thread Length (in) | Eye Dimensions (in) | | Working Load Limit (lbs) | Approx Weight Per 100 (lbs) |
|------------------------------------|--------------------|---------------------|------|--------------------------|-----------------------------|
| | | I.D. | O.D. | | |
| 1/4 X 2 | 1.50 | .50 | 1.00 | 650 | 6.00 |
| 1/4 X 4 | 2.50 | .50 | 1.00 | 650 | 13.50 |
| 5/16 X 2-1/4 | 1.50 | .62 | 1.25 | 1,200 | 18.75 |
| 5/16 X 4-1/4 | 2.50 | .62 | 1.25 | 1,200 | 25.00 |
| 3/8 X 2-1/2 | 1.50 | .75 | 1.50 | 1,550 | 24.33 |
| 3/8 X 4-1/2 | 2.50 | .75 | 1.50 | 1,550 | 37.50 |
| 3/8 X 6 | 2.50 | .75 | 1.50 | 1,550 | 43.75 |
| 1/2 X 3-1/4 | 1.50 | 1.00 | 2.00 | 2,600 | 50.00 |
| 1/2 X 6 | 3.00 | 1.00 | 2.00 | 2,600 | 62.50 |
| 1/2 X 8 | 3.00 | 1.00 | 2.00 | 2,600 | 75.00 |
| 1/2 X 10 | 3.00 | 1.00 | 2.00 | 2,600 | 88.00 |
| 1/2 X 12 | 3.00 | 1.00 | 2.00 | 2,600 | 100.00 |
| 5/8 X 4 | 2.00 | 1.25 | 2.50 | 5,200 | 101.25 |
| 5/8 X 6 | 3.00 | 1.25 | 2.50 | 5,200 | 120.00 |
| 5/8 X 8 | 3.00 | 1.25 | 2.50 | 5,200 | 131.00 |
| 5/8 X 10 | 3.00 | 1.25 | 2.50 | 5,200 | 162.50 |
| 5/8 X 12 | 4.00 | 1.25 | 2.50 | 5,200 | 175.00 |
| 3/4 X 4-1/2 | 2.00 | 1.50 | 3.00 | 7,200 | 168.60 |
| 3/4 X 6 | 3.00 | 1.50 | 3.00 | 7,200 | 184.50 |
| 3/4 X 8 | 3.00 | 1.50 | 3.00 | 7,200 | 200.00 |
| 3/4 X 10 | 3.00 | 1.50 | 3.00 | 7,200 | 237.50 |
| 3/4 X 12 | 4.00 | 1.50 | 3.00 | 7,200 | 251.94 |
| 3/4 X 15 | 5.00 | 1.50 | 3.00 | 7,200 | 300.00 |
| 7/8 X 5 | 2.50 | 1.75 | 3.50 | 10,600 | 275.00 |
| 7/8 X 8 | 4.00 | 1.75 | 3.50 | 10,600 | 325.00 |
| 7/8 X 12 | 4.00 | 1.75 | 3.50 | 10,600 | 400.00 |
| 1 X 6 | 3.00 | 2.00 | 4.00 | 13,300 | 425.00 |
| 1 X 9 | 4.00 | 2.00 | 4.00 | 13,300 | 452.00 |
| 1 X 12 | 4.00 | 2.00 | 4.00 | 13,300 | 550.00 |
| 1 X 18 | 7.00 | 2.00 | 4.00 | 13,300 | 650.00 |

See These In Our Stainless Steel Section

Ultimate Load is 5 Times the Working Load Limit. Working Load Limit applies to straight, inline pulls only.

Eye Nuts Self Colored



| Trade Size | Tap Size | Working Load Limit (lbs) | Weight Each (lbs) | Dimensions (in) | | | |
|------------|-----------|--------------------------|-------------------|-----------------|------|------|------|
| | | | | A | B | C | D |
| 1 | 1/4 - 20 | 520 | .09 | 1.25 | .75 | 1.00 | .25 |
| 2 | 3/8 - 16 | 1,250 | .17 | 1.62 | 1.00 | 1.20 | .31 |
| 3A | 1/2 - 13 | 2,250 | .28 | 2.00 | 1.25 | 1.44 | .38 |
| 4 | 5/8 - 11 | 3,600 | .60 | 2.50 | 1.50 | 1.92 | .50 |
| 5 | 3/4 - 10 | 5,200 | 1.00 | 3.00 | 1.75 | 2.28 | .63 |
| 6 | 7/8 - 9 | 7,200 | 1.65 | 3.50 | 2.00 | 2.50 | .75 |
| 7 | 1 - 8 | 10,000 | 2.69 | 4.00 | 2.25 | 2.92 | .88 |
| 8 | 1-1/4 - 7 | 15,500 | 3.87 | 4.50 | 2.50 | 3.35 | 1.00 |
| 9 | 1-3/8 - 6 | 18,500 | 5.00 | 5.00 | 2.75 | 4.00 | 1.13 |

Ultimate Load is 5 Times the Working Load Limit. Working Load Limit applies to straight, inline pulls only.