

Chain Links



- Not For Overhead Lifting
- Not For Securing Loads

Quick Links Electro Galvanized



Size (in)	Working Load Limit (lbs)	Weight per 100 pcs (lbs)	Dimensions (in)		
			Opening	Inside Width	Inside Length
1/8	400	2	0.188	0.375	1.125
3/16	660	4	0.250	0.500	1.500
1/4	880	8	0.281	0.563	1.750
5/16	1,760	16	0.375	0.688	2.313
3/8	2,650	24	0.438	0.750	2.438
1/2	3,300	56	0.625	0.938	3.133

Spring Snap Links Electro Galvanized



Size (in)	Working Load Limit (lbs)	Weight per 100 pcs (lbs)	Dimensions (in)		
			Opening	Max Inside Width	Inside Length
1/8	35	2	.24	.45	1.27
3/16	105	4	.28	.60	1.61
1/4	395	6	.32	.71	1.94
5/16	500	16	.40	.92	2.56
3/8	770	32	.58	1.20	3.19
1/2	900	60	.70	1.55	4.50

See These In Our Stainless Steel Section

Lap (Repair) Links Electro Galvanized



Size (in)	Working Load Limit (lbs)	Weight per 100 pcs (lbs)	Dimensions (in)	
			Inside Width	Inside Length
1/8	190	1.2	.30	.750
3/16	240	3.5	.50	1.00
1/4	400	6	.50	1.25
5/16	950	10	.75	1.50
3/8	1,250	22	.75	1.63
1/2	1,525	54	1.00	2.50

Cold Shuts Electro Galvanized



Size (in)	Working Load Limit (lbs)	Weight per 100 pcs (lbs)	Dimensions (in)	
			Inside Width	Inside Length
3/16	660	4.5	.34	0.93
1/4	880	8.0	.38	1.00
5/16	1,760	17	.44	1.20
3/8	2,220	23	.50	1.30
1/2	3,300	51	.75	1.56