

Welded Chain



LANDMANN
WIRE ROPE PRODUCTS

- Self Colored
- Zinc Plated
- Hot Dipped Galvanized



G30 Proof Coil Chain - NACM

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Feet Per Drum	Approx Weight per 100 ft (lbs)
1/8	400	1,600	0.25	0.94	2,500	20
3/16	800	3,200	0.30	0.98	1,600	40
1/4	1,300	5,200	0.38	1.24	800	66
5/16	1,900	7,600	0.44	1.29	550	86
3/8	2,650	10,600	0.55	1.38	400	142
1/2	4,500	18,000	0.72	1.79	200	242
5/8	6,900	27,600	0.79	2.20	150	357
3/4	10,600	42,400	0.98	2.76	100	560
7/8	12,800	51,200	1.08	3.03	80	675
1	17,900	71,600	1.25	3.58	60	924

Not Designed for Overhead Lifting

PAILS



G30 Proof Coil Chain - NACM Zinc Plated Pails

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Feet Per Pail	Approx Weight per Pail (lbs)
1/8	400	1,600	0.25	0.94	500	103
3/16	800	3,200	0.30	0.98	250	105
1/4	1,300	5,200	0.38	1.24	141	92
5/16	1,900	7,600	0.44	1.29	92	80
3/8	2,650	10,600	0.55	1.38	63	90

Not Designed for Overhead Lifting

G43 High Test Chain - NACM

- Self Colored
- Hot Dipped Galvanized



Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Feet Per Drum	Approx Weight per 100 ft (lbs)
1/4	2,600	7,800	0.38	1.24	800	66
5/16	3,900	11,700	0.44	1.29	550	86
3/8	5,400	16,200	0.55	1.38	400	142
1/2	9,200	27,600	0.72	1.79	200	242
5/8	13,000	39,000	0.79	2.20	150	357
3/4	20,200	60,600	0.98	2.76	100	560
7/8	24,500	73,500	1.08	3.03	80	675

Not Designed for Overhead Lifting