

G70 Transport Chain - NACM

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Feet Per Drum	Approx Weight per 100 ft (lbs)
1/4	3,150	12,600	0.38	1.24	800	66
5/16	4,700	18,800	0.44	1.29	550	86
3/8	6,600	26,400	0.55	1.38	400	142
1/2	11,300	45,200	0.72	1.79	200	242
5/8	15,800	63,200	0.79	2.20	150	357
3/4	24,700	98,800	0.98	2.76	100	560



- **Yellow Zinc Dichromate Finish**

Not Designed for Overhead Lifting

G80 Alloy Chain

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Maximum Inside Width (in)	Maximum Inside Length (in)	Minimum Weight per 100 ft (lbs)
9/32	3,500	14,000	0.430	0.900	72
5/16	4,500	18,000	0.500	1.040	92
3/8	7,100	28,400	0.600	1.260	127
1/2	12,000	48,000	0.768	1.640	226
5/8	18,100	72,400	0.945	2.020	365
3/4	28,300	113,200	1.180	2.520	520
7/8	34,200	136,800	1.300	2.770	720
1	47,700	190,800	1.540	3.280	925
1-1/4	72,300	289,200	1.890	4.030	1,465



- **Black Finish**

G80 Chain is designed for Overhead Lifting

Stainless Steel Chain T316

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Approx Weight per 100 ft (lbs)
1/8	500	2,000	0.25	0.94	25
3/16	930	3,730	0.30	0.98	42
1/4	1,570	6,280	0.30	1.24	65
5/16	2,400	9,600	0.38	1.29	86
3/8	3,550	14,200	0.55	1.38	140
1/2	6,500	26,000	0.62	1.79	260
5/8	9,800	39,200	0.79	2.20	358
3/4	15,000	60,000	0.98	2.85	560



Made with high percentages of nickel, chrome, and molybdenum
Not Designed for Overhead Lifting