

SS Screw Pin Anchor Shackle T316



Part #	Size (in)	Pin Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
SPASS1/4	1/4	5/16	1,000	.12
SPASS5/16	5/16	3/8	1,500	.18
SPASS3/8	3/8	7/16	2,000	.31
SPASS7/16	7/16	1/2	3,000	.48
SPASS1/2	1/2	5/8	4,000	.68
SPASS5/8	5/8	3/4	6,500	1.25
SPASS3/4	3/4	7/8	9,500	2.25
SPASS7/8	7/8	1"	12,000	3.30
SPASS1	1"	1-1/8	14,000	4.80

SS Screw Pin Chain Shackle T316



Part #	Size (in)	Pin Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
SPCSS1/4	1/4	5/16	1,000	.12
SPCSS5/16	5/16	3/8	1,500	.18
SPCSS3/8	3/8	7/16	2,000	.31
SPCSS7/16	7/16	1/2	3,000	.48
SPCSS1/2	1/2	5/8	4,000	.68
SPCSS5/8	5/8	3/4	6,500	1.25
SPCSS3/4	3/4	7/8	9,500	2.25
SPCSS7/8	7/8	1"	12,000	3.30
SPCSS1	1"	1-1/8	14,000	4.80

SS Bolt Type Anchor Shackle T316



Part #	Size (in)	Pin Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
SFTYASS1/4	1/4	5/16	1,000	.12
SFTYASS5/16	5/16	3/8	1,500	.18
SFTYASS3/8	3/8	7/16	2,000	.31
SFTYASS7/16	7/16	1/2	3,000	.48
SFTYASS1/2	1/2	5/8	4,000	.68
SFTYASS5/8	5/8	3/4	6,500	1.25
SFTYASS3/4	3/4	7/8	9,500	2.25
SFTYASS7/8	7/8	1"	12,000	3.30
SFTYASS1	1"	1-1/8	14,000	4.80