



6X7 Sand Line

Bright, Fiber Core

Size (in)	Approx. Wt per ft (lbs)	Nominal Breaking Load (lbs)
1/4	0.094	5,280
5/16	0.15	8,200
3/8	0.21	11,720
7/16	0.29	15,860
1/2	0.38	20,600
9/16	0.48	26,000
5/8	0.59	31,800
3/4	0.84	45,400
7/8	1.15	61,400



6 X 7 FC



6 X 7 FC

6X7 Trawl Cable


Galvanized, Heavy Lube, Fiber Core

Size (in)	Approx. Wt per ft (lbs)	Nominal Breaking Load (lbs)
1/4	0.094	4,760
5/16	0.15	7,380
3/8	0.21	10,540
7/16	0.29	14,280
1/2	0.38	18,540
9/16	0.48	23,400
5/8	0.59	28,600
3/4	0.84	40,800
7/8	1.15	55,200


6X21 Drill Line

Bright, Heavy Lube, Fiber Core

Size (in)	Approx. Wt per ft (lbs)	Nominal Breaking Load (lbs)
3/8	0.236	12,200
7/16	0.32	16,540
1/2	0.42	21,400
9/16	0.53	27,000
5/8	0.66	33,400
3/4	0.95	47,600
7/8	1.29	64,400
1"	1.68	83,600
1-1/8	2.13	105,200



6 X 21 FC



6 X 19S FC

6X19S Trawl Cable


Galvanized, Heavy Lube, Fiber Core

Size (in)	Approx. Wt per ft (lbs)	Nominal Breaking Load (lbs)
1/4	1.105	4,940
5/16	0.164	7,660
3/8	0.236	10,980
7/16	0.32	14,880
1/2	0.42	19,260
9/16	0.53	24,300
5/8	0.66	30,000
3/4	0.95	42,800
7/8	1.29	58,000

6X24 7HC Galvanized

Mooring Line

Size (in)	Approx. Wt per ft (lbs)	Nominal Breaking Load (lbs)
3/8	0.194	9,450
1/2	0.35	16,800
5/8	0.54	26,000
3/4	0.78	37,200
13/16	0.91	43,600
7/8	1.06	50,400
1"	1.38	65,600
1-1/16	1.56	73,800
1-1/8	1.75	82,400



6 X 24 7HC

