

Wire Rope Clips



WARNING! WIRE ROPE CLIPS ARE NOT DESIGNED FOR LOAD CARRYING PURPOSES OR OVERHEAD LIFTING, THEREFORE WORKING LOAD LIMITS HAVE NOT BEEN ESTABLISHED

Drop Forged Wire Rope Clips Hot Dipped Galvanized



Meets Federal Spec
FF-C-450D
Type 1, Class 1

ROPE SIZE in inches	MINIMUM No. of Clips	* Torque Ft. Lbs.	Length of Turn Back in Inches	Approx Wt per 100 pcs
1/8	2	34 in-lbs	3-1/4	6
3/16	2	66 in-lbs	3-3/4	10
1/4	2	12	4-3/4	18
5/16	2	18.5	5-1/4	30
3/8	2	25	6-1/2	47
7/16	2	35	7	76
1/2	3	35	11-1/2	80
9/16	3	50	12	104
5/8	3	50	12	106
3/4	4	100	18	150
7/8	4	140	19	212
1"	5	140	26	260
1-1/8	6	140	34	290
1-1/4	7	275	44	430
1-3/8	7	275	44	460
1-1/2	8	275	54	540
1-5/8	8	420	58	700
1-3/4	8	590	61	925
2"	8	750	71	1,300
2-1/4	8	750	73	1,600
2-1/2	9	750	84	1,900

* 1/8" & 3/16" torque is in inch-lbs. All other sizes in foot-lbs.

See These In Our
Stainless Steel
Section

Malleable Wire Rope Clips Electro Galvanized



Meets Federal Spec
FF-C-450D
Type 1, Class 2

ROPE SIZE in inches	MINIMUM No. of Clips	* Torque Ft. Lbs.	Length of Turn Back in Inches	Approx Wt per 100 pcs
1/16	3	2	4	3.5
1/8	3	2	4-3/4	3.8
3/16	3	2.67	5-1/2	6.3
1/4	3	12	7	11.8
5/16	3	12	7-3/4	13
3/8	3	18.5	9-1/2	23
7/16	4	18.5	10-1/4	23
1/2	4	25	15-1/2	38
9/16	4	35	16	44
5/8	4	35	16	57
3/4	5	50	22-1/4	78
7/8	5	100	23-1/2	120
1"	6	100	31	150
1-1/8	7	140	39	263
1-1/4	8	140	50	315

