


# Wire Rope Thimbles



## Heavy Duty Thimbles Hot Dipped Galvanized

Rope Diameter	Weight Each (lbs)	Dimensions			
		A	B	C	D
1/4	.07	2.19	1.62	1.50	.88
5/16	.12	2.50	1.88	1.81	1.06
3/8	.22	2.88	2.12	2.12	1.12
7/16	.35	3.25	2.38	2.38	1.25
1/2 - 9/16	.51	3.62	2.75	2.75	1.50
5/8	.76	4.25	3.25	3.12	1.75
3/4	1.58	5.00	3.75	3.81	2.00
7/8	1.77	5.50	4.25	4.25	2.25
1"	3.13	6.12	4.50	4.75	2.50
1-1/8 - 1-1/4	4.00	7.00	5.12	5.88	2.88
1-1/4 - 1-3/8	8.86	9.08	6.50	6.81	3.50
1-3/8 - 1-1/2	12.94	9.00	6.25	7.12	3.50
1-5/8	17.00	11.25	8.00	8.12	4.00
1-3/4	17.75	12.19	9.00	8.50	4.50
1-7/8 - 2"	27.75	15.12	12.00	10.38	6.00
2-1/4	39.50	17.50	14.00	11.88	7.00
2-1/2	60.50	18.40	16.75	11.78	8.00




Meets Federal Spec FF-T-276C, Type III

## Standard Thimbles Hot Dipped Galvanized & Zinc Plated

Rope Diameter (in)	Weight per 100 pcs (lbs)	Dimensions			
		A	B	C	D
1/8	3.50	1.94	1.31	1.06	.69
3/16	3.50	1.94	1.31	1.06	.69
1/4	3.50	1.94	1.31	1.06	.69
5/16	4.00	2.13	1.50	1.25	.81
3/8	6.70	2.38	1.63	1.47	.94
7/16	11.40	2.47	1.71	1.62	1.03
1/2	12.50	2.75	1.88	1.75	1.13
5/8	34.50	3.50	2.25	2.38	1.38
3/4	47.10	3.75	2.50	2.69	1.63
7/8	84.60	5.00	3.50	3.19	1.88
1	97.50	5.69	4.25	3.75	2.50
1-1/8 - 1-1/4	175.00	6.25	4.50	4.31	2.75

See These In Our Stainless Steel Section



Meets Federal Spec FF-T-276C, Type II

