

# Eye Bolts



**Ultimate Load is 5 Times the Working Load Limit.  
Working Load Limit applies to straight, inline pulls only.**

## Shoulder Nut Eye Bolts **Drop Forged, Hot Dipped Galvanized**



Shank Diameter X Shank Length (in)	Thread Length (in)	Eye Dimensions (in)		Working Load Limit (lbs)	Approx Weight Per 100 (lbs)
		I.D.	O.D.		
1/4 X 2	1.50	.50	.88	650	6.60
1/4 X 4	2.50	.50	.88	650	9.10
5/16 X 2-1/4	1.50	.62	1.12	1,200	12.50
5/16 X 4-1/4	2.50	.62	1.12	1,200	18.80
3/8 X 2-1/2	1.50	.75	1.38	1,550	21.40
3/8 X 4-1/2	2.50	.75	1.38	1,550	25.30
1/2 X 3-1/4	1.50	1.00	1.75	2,600	42.60
1/2 X 6	3.00	1.00	1.75	2,600	56.80
5/8 X 4	2.00	1.25	2.25	5,200	68.60
5/8 X 6	3.00	1.25	2.25	5,200	102.40
3/4 X 4-1/2	2.00	1.50	2.75	7,200	144.50
3/4 X 6	3.00	1.50	2.75	7,200	167.50
7/8 X 5	2.50	1.75	3.25	10,600	225.00
1 X 6	3.00	2.00	3.75	13,300	366.30
1 X 9	4.00	2.00	3.75	13,300	422.50
1-1/4 X 8	4.00	2.50	4.50	21,000	650.00
1-1/4 X 12	4.00	2.50	4.50	21,000	795.00
1-1/2 X 15	6.00	3.00	5.50	24,000	1425.00

**See These In Our  
Stainless Steel  
Section**

## Machinery Eye Bolts **Drop Forged, Self Colored**



Shank Diameter X Shank Length (in)	Trade Number	Thread Length (in)	Eye Dimensions (in)		Working Load Limit (lbs)	Approx Weight Per 100 (lbs)
			I.D.	O.D.		
1/4 X 1	21	1.00	.75	1.13	650	5
5/16 X 1-1/8	22	1.12	.88	1.38	1,200	9
3/8 X 1-1/4	23	1.25	1.00	1.62	1,550	15
7/16 X 1-3/8	24	1.37	1.09	1.84	1,800	21
1/2 X 1-1/2	25	1.50	1.19	1.95	2,600	28
9/16 X 1-5/8	26	1.62	1.28	2.28	3,200	35
5/8 X 1-3/4	27	1.75	1.38	2.38	5,200	55
3/4 X 2	28	2.00	1.50	2.76	7,200	96
7/8 X 2-1/4	29	2.25	1.75	3.25	10,600	154
1 X 2-1/2	30	2.50	2.00	3.76	13,300	218
1-1/4 X 3	31	3.00	2.50	4.50	21,000	380
1-1/2 X 3-1/2	32	3.50	2.50	5.18	21,000	700