

Chain Links

- Not For Overhead Lifting
- Not For Securing Loads



Quick Links Electro Galvanized



| Size (in) | Working Load Limit (lbs) | Weight per 100 pcs (lbs) | Dimensions (in) | | |
|-----------|--------------------------|--------------------------|-----------------|--------------|---------------|
| | | | Opening | Inside Width | Inside Length |
| 1/8 | 220 | 2 | 0.188 | 0.375 | 1.125 |
| 3/16 | 520 | 4 | 0.250 | 0.500 | 1.500 |
| 1/4 | 750 | 8 | 0.281 | 0.563 | 1.750 |
| 5/16 | 1,540 | 16 | 0.375 | 0.688 | 2.313 |
| 3/8 | 1,800 | 24 | 0.438 | 0.750 | 2.438 |
| 1/2 | 3,300 | 56 | 0.625 | 0.938 | 3.133 |

RoHS compliant Quick Links available

Spring Snap Links Electro Galvanized



| Size (in) | Working Load Limit (lbs) | Weight per 100 pcs (lbs) | Dimensions (in) | | |
|-----------|--------------------------|--------------------------|-----------------|------------------|---------------|
| | | | Opening | Max Inside Width | Inside Length |
| 1/8 | 200 | 2 | .24 | .45 | 1.27 |
| 3/16 | 220 | 4 | .28 | .60 | 1.61 |
| 1/4 | 260 | 6 | .32 | .71 | 1.94 |
| 5/16 | 500 | 16 | .40 | .92 | 2.56 |
| 3/8 | 770 | 32 | .58 | 1.20 | 3.19 |
| 1/2 | 1,200 | 60 | .70 | 1.55 | 4.50 |

RoHS compliant Snap Links available

Lap (Repair) Links Electro Galvanized

See These In Our Stainless Steel Section



| Size (in) | Working Load Limit (lbs) | Weight per 100 pcs (lbs) | Dimensions (in) | |
|-----------|--------------------------|--------------------------|-----------------|---------------|
| | | | Inside Width | Inside Length |
| 1/8 | 190 | 1.2 | .30 | .750 |
| 3/16 | 240 | 3.5 | .50 | 1.00 |
| 1/4 | 400 | 6 | .50 | 1.25 |
| 5/16 | 950 | 10 | .75 | 1.50 |
| 3/8 | 1,250 | 22 | .75 | 1.63 |
| 1/2 | 1,525 | 54 | 1.00 | 2.50 |

Cold Shuts Electro Galvanized



| Size (in) | Working Load Limit (lbs) | Weight per 100 pcs (lbs) | Dimensions (in) | |
|-----------|--------------------------|--------------------------|-----------------|---------------|
| | | | Inside Width | Inside Length |
| 3/16 | 660 | 4.5 | .34 | 0.93 |
| 1/4 | 880 | 8.0 | .38 | 1.00 |
| 5/16 | 1,760 | 17 | .44 | 1.20 |
| 3/8 | 2,220 | 23 | .50 | 1.30 |
| 1/2 | 3,300 | 51 | .75 | 1.56 |

