



G70 Transport Chain - NACM



- Yellow Zinc Dichromate Finish

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Minimum Inside Width (in)	Maximum Inside Length (in)	Feet Per Drum	Approx Weight per 100 ft (lbs)
1/4	3,150	12,600	0.38	1.24	800	66
5/16	4,700	18,800	0.44	1.29	550	86
3/8	6,600	26,400	0.55	1.38	400	142
1/2	11,300	45,200	0.72	1.79	200	242

Not Designed for Overhead Lifting

G80 Alloy Chain



- Black Finish

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Maximum Inside Width (in)	Maximum Inside Length (in)	Minimum Weight per 100 ft (lbs)
9/32	3,500	14,000	0.386	0.827	77
5/16	4,500	18,000	0.437	0.945	100
3/8	7,100	28,400	0.555	1.181	155
1/2	12,000	48,000	0.740	1.535	260
5/8	18,100	72,400	0.909	1.900	384

Designed for Overhead Lifting

G100 Alloy Chain



- Powder Coated Green

Chain Size (in)	Working Load Limit (lbs)	Minimum Breaking Strength (lbs)	Maximum Inside Width (in)	Maximum Inside Length (in)	Minimum Weight per 100 ft (lbs)
9/32	4,300	17,200	0.382	0.827	79
5/16	5,700	22,800	0.437	0.945	100
3/8	8,800	35,200	0.531	1.181	165
1/2	15,000	60,000	0.709	1.535	272
5/8	22,600	90,400	0.878	1.900	404

Designed for Overhead Lifting