



## Precision Formed® SS Lifting Eye Bolt w/Nut T316



Part #	Thread Pitch (in)	Shank Length (in)	Eye Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
EBSSL1/4-1	1/4-20	1-9/16	9/16	500	.08
EBSSL1/4-2	1/4-20	2-5/16	9/16	500	.09
EBSSL1/4-3	1/4-20	3-1/8	9/16	500	.09
EBSSL1/4-4	1/4-20	4	9/16	500	.10
EBSSL5/16-1	5/16-18	2-5/16	3/4	900	.16
EBSSL5/16-2	5/16-18	3-1/8	3/4	900	.17
EBSSL5/16-3	5/16-18	4	3/4	900	.19
EBSSL5/16-4	5/16-18	4-3/4	3/4	900	.21
EBSSL3/8-1	3/8-16	3-1/8	1	1,400	.31
EBSSL3/8-2	3/8-16	4	1	1,400	.32
EBSSL3/8-3	3/8-16	4-3/4	1	1,400	.34
EBSSL1/2-1	1/2-13	4	1-5/32	2,200	.54
EBSSL1/2-2	1/2-13	4-3/4	1-5/32	2,200	.60

## Precision Formed® SS Machinery Eye Bolt w/Nut T316



Part #	Thread Pitch (in)	Shank Length (in)	Eye Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
EBMSS1/4	1/4-20	1/2	5/8	400	.05
EBMSS5/16	5/16-18	5/8	3/4	800	.07
EBMSS3/8	3/8-16	3/4	1	1,350	.14
EBMSS1/2	1/2-13	1	1-1/4	2,100	.30

## Precision Formed® SS Eye Nut T316



Part #	Thread Pitch (in)	Eye Diameter (in)	Working Load Limit (lbs)	Weight Ea (lbs)
ENSS1/4	1/4-20	5/8	400	.05
ENSS5/16	5/16-18	3/4	800	.07
ENSS3/8	3/8-16	1	1,350	.14
ENSS1/2	1/2-13	1-1/4	2,100	.30
ENSS5/8	5/8-11	1-3/8	3,800	.45
ENSS3/4	3/4-10	1-9/16	6,200	.80